



# Bobcat®

## **ECONOMICAL. MANEUVERABLE. POWERFUL. 2000 PLATFORM COMPACT TRACTORS**

2000 platform tractors are available with manual shift or hydrostatic transmissions. Manual is effective for traveling longer distances at a consistent speed. Hydrostatic allows fast and intuitive direction changes for loader work and maneuvering around buildings and trees. The 2000 platform open-cab models make it convenient to climb on and off the tractor as needed.

The 2500 tractor models deliver all the benefits of the other 2000 platform tractors, plus an independent PTO on the CT2025, CT2035 and CT2040 or live PTO on the CT2535 and CT2540 for more productivity with less fatigue. The 2500 models also include a deluxe cab for unbeatable comfort for working during hot summer days or frigid winters.



### **MANUAL SYNCHRO SHUTTLE TRANSMISSION OR HYDROSTATIC TRANSMISSION (3-RANGE HST)**

The economical, reliable manual-shift transmission requires you to stop to change between nine forward gears and three reverse gears. It's the classic tractor transmission you might remember if you grew up on the farm. It works well for jobs that require a constant speed, such as mowing, tilling or spraying.

For maximum ease of use and fast, simple direction changes, choose the hydrostatic (HST) transmission. It is extremely effective for frequent front-end loader work, mowing or maneuvering in wooded areas while clearing brush. Instead of gears, a hydrostatic transmission uses hydraulic pressure to change your speed and range. You only need to stop moving if you want to change your range.

### **HIGH GROUND CLEARANCE**

A high minimum ground clearance enables you to keep working in uneven terrain or in wet, muddy conditions.

### **POWER STEERING**

Power steering adds near-effortless maneuverability and automotive-style comfort to your tractor's operation.

### **SINGLE FRONT-END LOADER JOYSTICK**

Control all loader functions with a single lever. When released, the lever automatically returns to the neutral position and the loader stops in place.

### **3-POINT CONTROL LEVER**

The control lever assists with implement hookup, allowing you to easily raise and lower lift arms.

Model	CT2025 HST	CT2025 MST	CT2035 HST	CT2035 MST	CT 2535 HST	CT2040 HST	CT2040 MST	CT2540 HST
<b>Engine</b>	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel
Gross Horsepower	24.5 hp (18.2 kW)	24.5 hp (18.2 kW)	34.9 hp (26.0 kW)	34.9 hp (26.0 kW)	34.9 hp (26.0 kW)	39.6 hp (29.5 kW)	39.6 hp (29.5 kW)	37.6 hp (28.0 kW)
No. of Cylinders	3	3	3	3	3	3	3	3
Total Displacement	100 cu. in. (1.6 L)	100 cu. in. (1.6 L)	111.4 cu. in. (1.8 L)	111.4 cu. in. (1.8 L)	111.4 cu. in. (1.8 L)	111.4 cu. in. (1.8 L)	111.4 cu. in. (1.8 L)	111.4 cu. in. (1.8 L)
Fuel Tank Capacity	9.0 gal. (34.1 L)	9.0 gal. (34.1 L)	9.0 gal. (34.1 L)	9.0 gal. (34.1 L)	9.0 gal. (34.1 L)	9.0 gal. (34.1 L)	9.0 gal. (34.1 L)	9.0 gal. (34.1 L)
<b>3-Point, PTO &amp; Hydraulics</b>								
3-Point Hitch	Category 1	Category 1	Category 1	Category 1	Category 1	Category 1	Category 1	Category 1
3-Point Lift Capacity*	1631 lb. (740 kg)	1631 lb. (740 kg)	1631 lb. (740 kg)	1631 lb. (740 kg)	1631 lb. (740 kg)	1631 lb. (740 kg)	1631 lb. (740 kg)	1631 lb. (740 kg)
3-Point Link Stabilizers	Turnbuckle	Turnbuckle	Turnbuckle	Turnbuckle	Telescoping	Turnbuckle	Turnbuckle	Telescoping
Lift Control Type	Hydraulic Position Control System	Hydraulic Position Control System	Hydraulic Position Control System	Hydraulic Position Control System	Hydraulic Position Control System	Hydraulic Position Control System	Hydraulic Position Control System	Hydraulic Position Control System
Lifting Rod	Turnbuckle	Turnbuckle	Turnbuckle	Turnbuckle	Crank	Turnbuckle	Turnbuckle	Crank
Lower Links	Fixed	Fixed	Fixed	Fixed	Telescopic	Fixed	Fixed	Telescopic
Mid-PTO	Optional: 1976 rpm	Optional: 1976 rpm	Optional: 1988 rpm	Optional: 1988 rpm	Optional: 1988 rpm	Optional: 1988 rpm	Optional: 1988 rpm	Optional: 1988 rpm
PTO Horsepower	21.8 hp (16.3 kW)	22.2 hp (16.6 kW)	29.4 hp (21.9 kW)	30.8 hp (23.0 kW)	29.4 hp (21.9 kW)	31.9 hp (23.8 kW)	34.9 hp (26.0 kW)	31.9 hp (23.8 kW)
Rear Hydraulics	2 Pairs Opt	2 Pairs Opt	2 Pairs Opt	2 Pairs Opt	2 Pairs Std	2 Pairs Opt	2 Pairs Opt	2 Pairs Std
Rear PTO	540 rpm	540 rpm	540 rpm	540 rpm	540 rpm	540 rpm	540 rpm	540 rpm
Rear PTO System	Live	Live	Live	Live	Independent	Live	Live	Independent
Total Hydraulic Pump Capacity	11.4 gpm (42.9 L/min.)	11.4 gpm (42.9 L/min.)	11.4 gpm (42.9 L/min.)	11.4 gpm (42.9 L/min.)	11.4 gpm (42.9 L/min.)	11.4 gpm (42.9 L/min.)	11.4 gpm (42.9 L/min.)	11.4 gpm (42.9 L/min.)
<b>Drive System</b>								
Transmission	3-Range HST	9F x 3R Manual	3-Range HST	9F x 3R Manual	3-Range HST	3-Range HST	9F x 3R Manual	3-Range HST
Brakes	Wet Multi-Disc	Wet Multi-Disc	Wet Multi-Disc	Wet Multi-Disc	Wet Multi-Disc	Wet Multi-Disc	Wet Multi-Disc	Wet Multi-Disc
Rear Differential Lock	Std	Std	Std	Std	Std	Std	Std	Std
Four-Wheel Drive	Std	Std	Std	Std	Std	Std	Std	Std
<b>Travel Speeds (w/ Ind. Tires)</b>								
Forward	9.7 mph (15.6 km/hr.)	9.4 mph (15.2 km/hr.)	14.4 mph (23.1 km/hr.)	14.1 mph (22.7 km/hr.)	14.4 mph (23.1 km/hr.)	14.4 mph (23.1 km/hr.)	14.1 mph (22.8 km/hr.)	14.4 mph (23.1 km/hr.)
Reverse	8.7 mph (14.0 km/hr.)	6.2 mph (9.9 km/hr.)	12.9 mph (20.8 km/hr.)	9.3 mph (14.9 km/hr.)	10.1 mph (16.2 km/hr.)	12.9 mph (20.8 km/hr.)	9.3 mph (14.9 km/hr.)	10.1 mph (16.2 km/hr.)
<b>Dimensions</b>								
Overall Length (w/ 3 pt.)	120.9 in. (3070 mm)	120.9 in. (3070 mm)	120.9 in. (3070 mm)	120.9 in. (3070 mm)	120.9 in. (3070 mm)	120.9 in. (3070 mm)	120.9 in. (3070 mm)	120.9 in. (3070 mm)
Overall Width (w/ industrial tires)	63.4 in. (1610 mm)	63.4 in. (1610 mm)	63.4 in. (1610 mm)	63.4 in. (1610 mm)	63.0 in. (1600 mm)	63.4 in. (1610 mm)	63.4 in. (1610 mm)	63.0 in. (1600 mm)
Overall Height	91.5 in. (2324 mm)	91.5 in. (2324 mm)	91.5 in. (2324 mm)	91.5 in. (2324 mm)	91.0 in. (2311 mm)	91.5 in. (2324 mm)	91.5 in. (2324 mm)	91.0 in. (2311 mm)
Wheelbase	65.7 in. (1670 mm)	65.7 in. (1670 mm)	65.7 in. (1670 mm)	65.7 in. (1670 mm)	65.7 in. (1670 mm)	65.7 in. (1670 mm)	65.7 in. (1670 mm)	65.7 in. (1670 mm)
Ground Clearance	11.5 in. (292 mm)	11.5 in. (292 mm)	11.5 in. (292 mm)	11.5 in. (292 mm)	12.3 in. (311 mm)	11.5 in. (292 mm)	11.5 in. (292 mm)	12.3 in. (311 mm)
Weight	2634 lb. (1195 kg)	2634 lb. (1195 kg)	3005 lb. (1363 kg)	3005 lb. (1363 kg)	3585 lb. (1626 kg)	3005 lb. (1363 kg)	3005 lb. (1363 kg)	3585 lb. (1626 kg)
<b>Steering</b>								
	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering
Inside Turning Radius	96.5 in. (2450 mm)	96.5 in. (2450 mm)	96.5 in. (2450 mm)	96.5 in. (2450 mm)	106.2 in. (2700 mm)	96.5 in. (2450 mm)	96.5 in. (2450 mm)	106.2 in. (2700 mm)
Tilt Steering Wheel	—	—	—	—	Std	—	—	Std
<b>Safety Equipment</b>								
Safety Interlock System (neutral start-operating)	Std	Std	Std	Std	Std	Std	Std	Std
Fold-Down ROPS (roll-over protective structure)	Std	Std	Std	Std	—	Std	Std	—
Fully Retractable Seat Belt	Std	Std	Std	Std	Std	Std	Std	Std
<b>Features</b>								
Adjustable Seat	Std	Std	Std	Std	Std	Std	Std	Std
Cup Holder	Std	Std	Std	Std	Std	Std	Std	Std
Glow Plug Engine Preheat	Std	Std	Std	Std	Std	Std	Std	Std
Toolbox	Opt	Opt	Opt	Opt	Std	Opt	Opt	Std
Head Lights/Tail Lights/ Brake Lights	Std	Std	Std	Std	Std	Std	Std	Std
Cruise Control	Opt	Opt	Opt	Opt	Std	Opt	Opt	Std
Spark Arrestor Muffler	Opt	Std	Std	Std	Std	Std	Std	Std
Horn/Hazard Flasher/ Turn Signals	Std	Std	Std	Std	Std	Std	Std	Std
Rear Working Light	Opt	Opt	Opt	Opt	Std	Opt	Opt	Std
Side Mirror	Opt	Opt	Opt	Opt	Std	Opt	Opt	Std
Enclosed Cab With Heat/AC	—	—	—	—	Std	—	—	Std

\*Note: Hydraulic 3 pt. lift capacity will vary depending on lift point height.

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual Bobcat equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.

**DOOSAN**

**Bobcat Company is a member of the Doosan Group.** Doosan is a global leader in construction, grounds maintenance and material handling equipment, power and water solutions, and engineering that has proudly served customers and communities for more than a century. Bobcat®, the Bobcat logo and the colors of the Bobcat machine are registered trademarks of Bobcat Company in the United States and various other countries. ©2023 Bobcat Company. All rights reserved.

**B-2276 (05/23)**  
EP-3M-0523-3650-F

**Bobcat Company**  
250 East Beaton Drive • West Fargo, ND 58078  
**Bobcat.com**



**Bobcat®**

**One Tough Animal.**