



# Bobcat®

## **DISH OUT MORE HORSEPOWER. STACK UP MORE ACCOMPLISHMENTS. BOBCAT UT6573 UTILITY TRACTOR**

The Bobcat® UT6573 adds more horsepower. More comfort. More of everything you need to handle the biggest challenges on your property or jobsite. From inside your comfortable cab, you'll command the ultimate in utility tractor performance, powered by a 73-horsepower Tier 4 diesel engine. Hook up heavy-duty Category 2 3-point implements. Dig into dense, heavy materials with the self-leveling front-end loader. Connect a variety of Bobcat attachments to your front-end loader and customize your machine for countless tasks. It's the ultimate tractor for your productivity.

### **COMFORTABLE ENCLOSED CAB WITH HEAT AND AIR CONDITIONING**

Stay out of the elements and surround yourself in comfort with the fully enclosed cab. The UT6573 cab is also radio-ready. Controls, gauges and buttons are thoughtfully laid out – easy to find and use. An illuminated dashboard helps you operate and monitor performance when natural light levels are low.



### **LED WORK LIGHTS**

Bright LED headlights illuminate the job for evening work and other low-light conditions. Additional LED work lights on the front and rear provide extra illumination and visibility for the job.

### **MECHANICAL SELF-LEVELING LOADER**

The standard mechanical self-leveling loader automatically keeps your load level throughout its full range of loader motion. Its ease of operation is ideal for keeping a level bucket or pallet fork and minimizing spillage. The front-end loader is easy to hook up and remove, saving you installation time.

### **POWERSHUTTLE TRANSMISSION**

The UT6573 features a 12x12 powershuttle transmission that has three ranges. Each range offers four powerful gears in both forward and reverse. With your electronic hand clutch, you have smooth, easy shifting from gear to gear, giving you high torque or faster travel speeds on command.

### **REAR PTO AND CATEGORY 2 3-POINT HITCH**

Equipped with the Category 2 3-point hitch, a 540 rpm PTO and a pair of rear remote hydraulics (plus the option to have a second or third), the UT6573 tractor is packed with major productivity potential. Use both non-powered and PTO-powered implements to take on an endless variety of tasks on your property or jobsite.

# SPECIFICATIONS

Model	UT6573
<b>Engine</b>	
Emissions Tier (EPA)	Tier 4/Stage 5
Engine Make	Daedong
Engine Model	4HT-TP4A
Gross Horsepower	73.1 hp (54.5 kW)
No. of Cylinders	4
Total Displacement	148.6 cu. in. (2435 cc)
Fuel Tank Capacity	25.1 gal. (95.0 L)
RPM	2600
<b>3-Point, PTO &amp; Hydraulics</b>	
3-Point Hitch	Category 2
3-Point Lift Capacity*	3898 lb. (1768 kg)
Lift Control Type	Position With Draft Control
Mid-PTO	—
PTO Horsepower	56.3 hp (41.9 kW)
Rear PTO	540/540E rpm
Rear PTO System	Independent
Total Hydraulic Pump Capacity	19.2 gpm (72.7 L/min.)
Implement Hydraulic Flow	10.9 gpm (41.6 L/min.)
Steering Hydraulic Flow	8.2 gpm (31.1 L/min.)
<b>Drive System</b>	
Standard Transmission	3-Range Powershuttle With Electronic Clutch
Brakes	Wet Multi-Disc
Four-Wheel Drive	Std
Number of Forward Speeds	4
<b>Travel Speeds</b>	
Forward	19.9 mph (32.0 km/hr.)
Reverse	19.6 mph (31.5 km/hr.)



Model	UT6573
<b>Dimensions</b>	
Length	150.0 in. (3810 mm)
Width	83.5 in. (2120 mm)
Height	101.1 in. (2567 mm)
Wheelbase	83.9 in. (2131 mm)
Ground Clearance	12.3 in. (312 mm)
Weight	5960 lb. (2703 kg)
Front Tire Size	Front Industrial (Ag, Multi-Use) 12.5/80-18 (11.2-24, 340/80R18)
Rear Tire Size	Rear Industrial (Ag, Multi-Use) 18.4-24 (16.9-30, 480/80R26)
<b>Steering</b>	
Turning Radius	154.0 in. (3911 mm)
Outside Turning Diameter	321.0 in. (8153 mm)
Tilt Steering Wheel	Std
<b>Safety Equipment</b>	
Fold-Down ROPS (roll-over protective structure)	—
<b>Features</b>	
Suspension Seat	Std
Glow Plug Engine Preheat	Std
Cruise Control	Std
Spark Arrestor Muffler	Std
Horn	Std
<b>Loader Attachment</b>	
Loader Model	FL10
Loader Lift Height	129.0 in. (3276 mm)
Lift Capacity at Bucket Pivot	3212 lb. (1456 kg)
Bucket Width	81.0 in. (2057 mm)
Loader Control Valve and Joystick	Std

\*At 24 inches behind lift point.

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual Bobcat equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.

**DOOSAN**

**Bobcat Company is a member of the Doosan Group.** Doosan is a global leader in construction, grounds maintenance and material handling equipment, power and water solutions, and engineering that has proudly served customers and communities for more than a century. Bobcat®, the Bobcat logo and the colors of the Bobcat machine are registered trademarks of Bobcat Company in the United States and various other countries. ©2024 Bobcat Company. All rights reserved.



**B-3027 (05/24)**  
EP-XX-0524-13840-F

**Bobcat Company**  
250 East Beaton Drive • West Fargo, ND 58078  
**Bobcat.com**



**Bobcat®**

**One Tough Animal.**